

مولانا آزاد نیشنل اردو یونیورسٹی
مؤلانا آزااا نیشنل اردو یونیورسٹی

MAULANA AZAD NATIONAL URDU UNIVERSITY
(A Central University)



No. MANUU/CD/F.151/2019-20/60

Dated: 15/05/2019

Notice Inviting Quotation

NIO No. 04/MANUU/ES/F.151/2019-20/ dated: 15/05/2019

The Executive Engineer, MANUU Hyderabad invites on behalf of Vice-Chancellor, Sealed item rate quotations from CPWD contractors/reputed service agencies for the following work so as to reach this office upto 15:00 PM on 22/05/2019. The quotation will be opened on the same day at 15:30 PM. Blank quotation form can be obtain from this office during office hours in all working days and upto 14:00 PM on 22/05/2019.


Name of the Work: Repair work in UGC HRDC hostel building, MANUU Hyderabad.

| S.No. | Description of item | Qty | Unit | Rate | | Amount |
|---|---------------------|-----|------|--------|----------|--------|
| | | | | In fig | In words | |
| As per attached Schedule of Quantities | | | | | | |

Term and conditions:

1. The work shall be carried out as per CPWD Specifications 2009 Vol-I & II with up to date correction
2. The work should be completed within twenty (20) days from the date of Issue of Work Order.
3. The rates should be quoted in figures and words and inclusive of all taxes, duties and nothing will be paid extra.
4. Necessary recoveries of IT and GST as applicable will be deducted from the bill.
5. The payment will be made after satisfactory completion of work and as per actual measurements recorded.

CONTRACTOR
Address


Executive Engineer

Copy to :

1. The Office of the Registrar
2. Director CIT for uploading in the University website
3. Notice Board

Gachibowli, Hyderabad – 500 032.

☎ 09440236909; ☎ 040-23008468 & 23008320 (or) EPABX 23006612/13/14/15 Extn. 111 & 221.

e-mail: executive_engineer@manuu.edu.in

website: www.manuu.ac.in

Schedule of Quantities

Name of the work: *Repair works in UGC HRDC hostel building, MANUU Hyderabad.*

| S.No | Items | Quantity | Units | Rate | | Amount |
|-------|---|----------|-------|--------|----------|--------|
| | | | | in fig | in words | |
| 1 | Earth work in surface excavation not exceeding 30 cm in depth but exceeding 1.5 m in width as well as 10 sqm on plan including getting out and disposal of excavated earth upto 50 m and lift upto 1.5 m, as directed by Engineer-in-Charge | | | | | |
| 1.1 | All kinds of soil | 20 | Sqm | | | |
| 2 | Earth Excavating trenches of required width for pipes, cables, etc. including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering etc. and disposing of surplus excavated soil as directed, within a lead of 50 m : | | | | | |
| 2.1 | All kinds of soil | | | | | |
| 2.1.1 | Pipes, cables etc. exceeding 80mm dia, but not exceeding 300 mm dia | 30 | mtr | | | |
| 3 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level | | | | | |
| 3.1 | 1:5:10 (1 cement : 5 coarse sand (zone-III): 10 graded stone aggregate 40 mm nominal size) | 2 | cum | | | |
| 3.2 | 1:2:10(1 cement : 2 coarse sand (zone-III) : 4 graded stone aggregate 20 mm nominal size) | 2 | cum | | | |
| 4 | Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour | | | | | |
| 4.1 | Two coats | 180 | sqm | | | |
| 5 | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: | | | | | |
| 5.1 | One or more coats on old work | 50 | Sqm | | | |

| S.No | Items | Quantity | Units | Rate | | Amount |
|-------|--|----------|-------|--------|----------|--------|
| | | | | in fig | in words | |
| 6 | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead | | | | | |
| 6.1 | For thickness of tiles 10 mm to 25 mm | 2 | sqm | | | |
| 7 | Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with line sand etc. all complete as per the direction of Engineer-in-charge | 2 | sqm | | | |
| 8 | Providing, laying and jointing glazed stoneware pipes class SP-1 with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. complete | | | | | |
| 8.1 | 150 mm diameter | 25 | mtr | | | |
| 9 | Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm size (inside) the weight of cover to be not less than 4.50 kg and frame to be not less than 2.70 kg as per standard design | | | | | |
| 9.1 | 180x150 mm size P type | | | | | |
| 9.1.1 | With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 | 2 | each | | | |
| 10 | Providing and laying non-pressure NP2 class (light duty) R.C.C. pipes with collars jointed with stiff mixture of cement mortar in the proportion of 1:2 (1 cement : 2 fine sand) including testing of joints etc. complete | | | | | |
| 10.1 | 250 mm dia. R.C.C. pipe | 2 | mtr | | | |

| S.No | Items | Quantity | Units | Rate | | Amount |
|------|--|----------|-------|--------|----------|--------|
| | | | | in fig | in words | |
| 11 | Constructing brick masonry manhole in cement mortar 1:4 (1 cement : 4 coarse sand) with R.C.C. top slab with 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design | | | | | |
| 11.1 | Inside size 90x80 cm and 45 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) | | | | | |
| 11.2 | With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 | 1 | Each | | | |
| | Total | | | | | |

Term and conditions:

- 1 The work shall be carried out as per CPWD Specifications 2009 Vol-I & II with up to date correction
- 2 The work should be completed within twenty (20) days from the date of Issue of Work Order.
- 3 The rates should be quoted in figures and words and inclusive of all taxes, duties and nothing will be paid extra.
- 4 Necessary recoveries of IT and GST as applicable will be deducted from the bill.

Contractor
Address


Executive Engineer