
मोलावा आज़ाद वेशवल उर्दू यूविवर्सिटी مولانا آزاد ليشنل أر دويو نيورسي

MAULANA AZAD NATIONAL URDU UNIVERSITY





No. MANUU/CD/F.82/2021-22/144

Dated: 29/10/2021

Notice Inviting Ouotation

NIQ No.05/MANUU/CD/2020-21/

Sealed item rate quotations are invited for Repair/renovation works at Open Air Theatre, MANUU Campus, Hyderabad to reach the office of the Incharge Engineering Section, MANUU Gachibowli, Hyderabad up to 10.00 AM on or before 05/11/2021. The quotation will be opened on the same day at 10:30 AM. Blank quotation form can be downloaded from the website.

Name of the Work: Repair/renovation works at Open Air Theatre, MANUU Campus, Hyderabad.

S.No.	Description of item	Qty	Unit	Rate		Amount
				In fig	In words	
		1	ached Sch	-	Quantities	

Term and conditions:

- 1. The work shall be executed as per CPWD specification Vol-I &II as per manufacturer's specifications.
- 2 Time allowed is 07 days.
- 3. The payment shall be as per actual execution and measurement at site.
- The rates quoted are net including transportation at site and nothing extra shall be paid on account of taxes, octoria etc.
- 5. The Income tax shall be deducted as per applicable and notified by Govt.of India.

Contractor Sign Address I/c Engineering & CD Section

Copy to

- 1. The Office of the Registrar
- 2. Director CIT for uploading in the University website
- 3. Notice Board

मोलाना आज़ाद नेशनल उर्दू यूनिवर्सिटी حولانا آزوويو تحوري

MAULANA AZAD NATIONAL URDU UNIVERSITY

A Central University established by an Act of Parliament in 1998

Schedule of Quantity

Name of the work: Repair/Renovation works at Open Air Theatre in the MANUU Campus, Hyd.

Description	Qty	Unit	Rate		Amount
			in Fig	In words	Amount
Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing:					
1:3:6 (1 cement : 3 coarse sand (zone-III) : 6 graded stone aggregate 20 mm nominal size)	1.85	cum			
Providing and fixing sheet covering over expansion joints with iron screws as per design.				•	
Aluminium fluted strips 3.15 mm thick.					
150 mm wide	40.00	metre			
Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level.					
Cement mortar 1:3 (1 cement :3 coarse sand)	45.00	Sqm			
12 mm cement plaster of mix :					
1:4 (1 cement: 4 fine sand)	56.00	Sqm			
15 mm cement plaster on the rough side of single or half brick wall of mix :					
1:4 (1 cement: 4 fine sand)	30.00	Sqm			
Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :					
Two or more coats on new work	280.00	sqm			
	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:3:6 (1 cement : 3 coarse sand (zone-III) : 6 graded stone aggregate 20 mm nominal size) Providing and fixing sheet covering over expansion joints with iron screws as per design. Aluminium fluted strips 3.15 mm thick. 150 mm wide Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:3 (1 cement :3 coarse sand) 12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand) 15 mm cement plaster on the rough side of single or half brick wall of mix ; 1:4 (1 cement: 4 fine sand) Painting with synthetic enamel paint of approved brand and manufacture to give an even shade ;	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:3:6 (1 cement : 3 coarse sand (zone-III) : 6 graded stone aggregate 20 mm nominal size) Providing and fixing sheet covering over expansion joints with iron screws as per design. Aluminium fluted strips 3.15 mm thick. 150 mm wide 40.00 Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:3 (1 cement :3 coarse sand) 45.00 12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand) 56.00 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:3:6 (1 cement : 3 coarse sand (zone-III) : 6 graded stone aggregate 20 mm nominal size) Providing and fixing sheet covering over expansion joints with iron screws as per design. Aluminium fluted strips 3.15 mm thick. 150 mm wide Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:3 (1 cement :3 coarse sand) 12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand) 56.00 Sqm 15 mm cement plaster on the rough side of single or half brick wall of mix : 1:4 (1 cement: 4 fine sand) Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:3:6 (1 cement : 3 coarse sand (zone-III) : 6 graded stone aggregate 20 mm nominal size) Providing and fixing sheet covering over expansion joints with iron screws as per design. Aluminium fluted strips 3.15 mm thick. 150 mm wide Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:3 (1 cement :3 coarse sand) 45.00 Sqm 12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand) 56.00 Sqm Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:3:6 (1 cement : 3 coarse sand (zone-III) : 6 graded stone agergeate 20 mm nominal size) Providing and fixing sheet covering over expansion joints with iron screws as per design. Aluminium fluted strips 3.15 mm thick. 1:50 mm wide Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:3 (1 cement : 3 coarse sand) 45.00 Sqm 1:2 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand) 7:5 mm cement plaster on the rough side of single or half brick wall of mix ; 1:4 (1 cement: 4 fine sand) Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :

S.No.	Description	Qty	******	Rate		Amount
			Unit	in Fig	In words	Amount
7	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	100.00	Sqm			
8	Distempering with 1st quality acrylic distemper, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.		-			
8.1	One coat.	500.00	Sqm			
8.1.2	Two coats.	650.00	Sqm			
9	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	1000	per litre			
10	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing					
10.1	25 mm nominal outer dia Pipes	30	metre			
11	Providing and fixing C.P. brass bib cock of approved quality conforming to 1S:8931:					
11.1	15 mm nominal bore	3	each			
12	Providing and fixing Mastic pads in the expansion joint	15.00	Sqm			

ontractor Sign ddress

I/c Engineering & CD Section