
मोलाना आज़ाद नेशनल उर्दू यूनिवर्सिटी रेंग्डर में हैं। ने स्थान

MAULANA AZAD NATIONAL URDU UNIVERSITY





No. MANUU/CD/F.98/2019-20/ 餐

Dated: 21/06/2019

Notice Inviting Quotation

NIQ No. 9 /MANUU/ES/F.98/2019-20/ dated: 21/06/2019

The Executive Engineer, MANUU Hyderabad invites on behalf of Vice-Chancellor, Sealed item rate quotations from CPWD contractors/reputed service agencies for the following work so as to reach this office upto 15:00 PM on 27/06/2019. The quotation will be opened on the same day at 15:30 PM. Blank quotation form can be obtain from this office during office hours in all working days and upto 14:00 PM on 27/06/2019.

Name of the Work: Repair & replacement of sewerage line at Type-III quarters at MANUU Hyderabad.

S.No.	Description of item	Qty	Unit		Rate	Amount
				In fig	In words	
	As per at	tached Sc	hedule	of Quan	tities	

Term and conditions:

- 1. The work shall be carried out as per CPWD Specifications 2009 Vol-I & II with up to date correction
- Time allowed is Twenty (20) days from the date of Issue of Work Order.
- 3. The rates quoted shall be inclusive of all taxes, duties and nothing will be paid extra.
- 4. Necessary recoveries of IT and GST as applicable will be deducted from the bill.
- The payment will be made after satisfactory completion of work and as per actual measurements recorded at site.

CONTRACTOR Address **Executive Engineer**

Copy to:

- 1. The Office of the Registrar
- Director CIT for uploading in the University website
- Notice Board

e-mail: executive engineer@manuu.edu.in

website: www.manuu.ac.in

Schedule of Quantities

Name of the Work: Repair and replacement of Sewerage line at Type -III quarter at MANUU, Hyderabad

S.No.	Description of item	Qty	Units	Rate		Amount
3.140.	Description of item	Qty	Cuits	in fig	in words	Amount
4	Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in-charge.					
1.1	All Kinds of Soil	15	cum			
2	Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m:					
2.1	All kinds of soil					
2.1.2	Pipes, cables etc. exceeding 80 mm dia. but not exceeding 300 mm dia	35	metre			
3	Providing, laying and jointing glazed stoneware pipes class SP-1 with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. complete :			(a) (b)		
3.1	150 mm diameter	35	metre			
4	Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) up to haunches of S.W. pipes including bed concrete as per standard design :					
4.1	150 mm diameter S.W. pipe	35	metre			
5	Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm size (inside) the weight of cover to be not less than 4.50 kg and frame to be not less than 2.70 kg as per standard design					
5.1	180x150 mm size P type					
5.1.2	With Common burnt clay F.P.S(non modular) bricks of class designation 7.5	2	Each			

S.No.	Description of item	Qty	Units		Rate	
			Cints	in fig	in words	Amount
6	Constructing brick masonry manhole in cement mortar 1:4 (1 cement: 4 coarse sand) with R.C.C. top slab with 1:2:4 mix (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement: 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design					
6.1	Inside size 90x80 cm and 45 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg)					
6.2	With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	2	Each			
	Total					

Terms and Conditions

- 1 The work shall be carried out as per CPWD Specifications 2009 Vol-I & II with up to date correction
- 2 Time allowed is twenty (20) days from the date of Issue of Work Order.
- 3 The rates quoted shall be inclusive of all taxes, duties and nothing will be paid extra.
- 4 Necessary recoveries of IT and GST as applicable will be deducted from the bill.
- 5 The payment will be made after satisfactory completion of work and as per actual measurements recorded at site.

CONTRACTOR Address Executive Engineer